



- Unmanaged Gigabit PoE Ethernet Switch
- 8x PoE (RJ45), Uplink 1x RJ45 + 1x SFP
- Support QOS WRR queue algorithm
- Support BPDU Frame and EAPOL
- Supports IEEE 802.3 /ab /u /x /az /af /at
- 10/100/1000 Full/Half-Duplex, MDI/MDI-X auto-detection
- 53.5VDC with Jack (<4W)
- Operating temperature ranges from -10° ~ +45°C
- IP40, Metal housing
- IEC 61000-4-2, level 4, ESD + IEC 61000-4-5, level4, surge
- Desktop and Wall Mounting

NETLANCE ES-P10G2-MUP

Gigabit Ethernet Switch



ETHERNET

Connector	9x RJ45 / 1x SFP
Ports	10
Uplink Port	1x RJ45 / 1x SFP
PoE Port	8x RJ45 PoE (Max 120W, 30W for single PoE port)
Transmission Rate	10/100/1000 Mbps
Standards	IEEE 802.3 /ab /u /x /az /af /at
Auto MDI/MDI-X	Yes
VLAN mode	Supported (through switch)
MAC Address Table	4K

POWER

Input Voltage	53.5 VDC
Input Current	1.22A
Power Consumption	<5 W Max (w/o PoE)
Connector	Jack

PHYSICAL CHARACTERISTICS

Housing	IP40 protection, Metal housing
Dimension (W x H x D)	200mm x 100mm x 26mm
Weight	0.35Kg
Installation	Desktop and Wall Mount
Reset Button	No
Warranty	1 year

ENVIRONMENTAL LIMITS

Operating Temperature	-10°C ~ +45°C (14° ~ 113°F)
Storage Temperature	-40°C ~ +70°C (-40° ~ 158°F)
Ambient Relative Humidity	5 ~ 90%RH (Non-condensing)

*All product information may subject to change without prior notice.

*The rights of all brand names, product names and trademarks belong to their respective owners.

SARC ITALIA SRL

Strada Albareto, 503 - 41122 Modena - ITALY
Tel. +39 059 8751076 Fax. +39 059 8751025

Website: www.indatech.it

Email: info@indatech.it

Copyright © 2024 INDATECH. All rights reserved.